

MINIMILL

Nut- und Formzirkularfräsen

groove milling by circular interpolation


Typ Z622

metrisches ISO-Gewinde, Vollprofil, außen

metric ISO-thread, full profile, external

Steigung 1.5 - 4.0

pitch 1.5 - 4.0



Abmessungen in mm

dimensions in mm

Bestellnummer part number	Steigung P pitch P	S	E	R	Ø DS	b ± 0.01	H1	Zähnezahl number of teeth	K10F AL41F P18C	für Frälerschaft for milling shank
Z622.E0815.02	1.50	6.25	5.35	0.22	21.7	1.316	0.92	6	●	ZH22...
Z622.E0917.02	1.75	6.25	5.25	0.25	21.7	1.524	1.07	6	●	
Z622.E1020.02	2.00	6.25	5.10	0.29	21.7	1.755	1.23	6	●	
Z622.E1630.02	3.00	6.05	4.50	0.43	21.7	2.621	1.84	6	●	
Z622.E2140.02	4.00	6.05	4.00	0.58	21.7	3.499	2.45	6	●	

Weitere HM Sorten können Sie in der Sortenübersicht im Kapitel "Technische Hinweise" und der Preisliste finden.

Bestellbeispiel:
für Sorte AL41F:
Z622.E0815.02/AL41F

More carbide grades you can find in the grades summary in the chapter "technical instructions" and in the price list.

order-example:
grade AL41F:
Z622.E0815.02/AL41F